


### 650V N-Channel Power MOSFET

#### Features

- High Voltage:  $BV_{DSS}=650V(\text{Min.})$
- $I_D : 7A$
- Robust high voltage termination
- Avalanche energy specified
- Fast diode recovery time

#### Application

- Ballast Bridge
- Switch Mode Power Supplier
- Power Factor Correction
- Lighting



#### Ordering Information

Type NO	Marking	Package Code
WMF7N65U	7N65FU	TO-220F

#### Absolute maximum ratings ( $T_C=25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Rating	Unit	
Drain-source voltage	$V_{DSS}$	650	V	
Gate-source voltage	$V_{GSS}$	$\pm 30$	V	
Drain current (DC) *	$I_D$	$T_C=25^\circ\text{C}$	7.0	A
		$T_C=100^\circ\text{C}$	4.43	A
Drain current (Pulsed) *	$I_{DM}$	28	A	
Single avalanche energy ②	$E_{AS}$	92.9	mJ	
Repetitive avalanche current ①	$I_{AR}$	7.0	A	
Repetitive avalanche energy ①	$E_{AR}$	3.2	mJ	
Power dissipation	$P_D$	32	W	
Junction temperature	$T_J$	150	$^\circ\text{C}$	
Storage temperature range	$T_{stg}$	-55~150	$^\circ\text{C}$	

\* Limited by maximum junction temperature

Characteristic	Symbol	Typ.	Max	Unit	
Thermal resistance	Junction-case	$R_{th(J-C)}$	-	3.9	$^\circ\text{C}/\text{W}$
	Junction-ambient	$R_{th(J-A)}$	-	62.5	

**Electrical Characteristics** ( $T_C=25^\circ\text{C}$  unless otherwise noted)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	$BV_{DSS}$	$I_D=250\ \mu\text{A}, V_{GS}=0\text{V}$	650	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$I_D=250\ \mu\text{A}, V_{DS}=V_{GS}$	3.0	-	5.0	V
Drain-source cut-off current	$I_{DSS}$	$V_{DS}=650\text{V}, V_{GS}=0\text{V}$	-	-	1	$\mu\text{A}$
		$V_{DS}=650\text{V}, T_C=150^\circ\text{C}$			100	$\mu\text{A}$
Gate leakage current	$I_{GSS}$	$V_{DS}=0\text{V}, V_{GS}=\pm 30\text{V}$	-	-	$\pm 100$	nA
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS}=10\text{V}, I_D=3.5\text{A}$	-	1.2	1.4	$\Omega$
Forward transfer conductance ③	$g_{fs}$	$V_{DS}=10\text{V}, I_D=3.5\text{A}$	-	8.7	-	S
Input capacitance	$C_{iss}$	$V_{DS}=25\text{V}, V_{GS}=0\text{V}$ $f=1\ \text{MHz}$	-	1380	-	pF
Output capacitance	$C_{oss}$		-	90	-	
Reverse transfer capacitance	$C_{rss}$		-	9	-	
Turn-on delay time ③④	$t_{d(on)}$	$V_{DS}=325\text{V}, I_D=7\text{A}$ $R_G=25\ \Omega$	-	69	-	ns
Rise time ③④	$t_r$		-	37	-	
Turn-off delay time ③④	$t_{d(off)}$		-	130	-	
Fall time ③④	$t_f$		-	25	-	
Total gate charge ③④	$Q_g$	$V_{DS}=520\text{V}, V_{GS}=10\text{V}$ $I_D=7\text{A}$	-	21	26	nC
Gate-source charge ③④	$Q_{gs}$		-	9	-	
Gate-drain charge ③④	$Q_{gd}$		-	5	-	

**Source-Drain Diode Ratings and Characteristics** ( $T_C=25^\circ\text{C}$  unless otherwise noted)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Source current (DC)	$I_S$	Integral reverse diode in the MOSFET	-	-	7	A
Source current (Pulsed)	$I_{SM}$		-	-	28	
Forward voltage	$V_{SD}$	$V_{GS}=0\text{V}, I_{SD}=7\text{A}$	-	-	1.4	V
Reverse recovery time ③④	$t_{rr}$	$I_{SD}=7\text{A}, V_{GS}=0\text{V}$ $dI_F/dt=100\text{A}/\mu\text{s}$	-	410	-	ns
Reverse recovery charge ③④	$Q_{rr}$		-	1.7	-	$\mu\text{C}$

Note ;

1. Repetitive rating : Pulse width limited by safe operating area
2.  $L=10\text{mH}, I_{AS}=4\text{A}, V_{DD}=50\text{V}, R_G=25\ \Omega$ , Starting  $T_J=25^\circ\text{C}$
3. Pulse Test : Pulse width  $\leq 300\ \mu\text{s}$ , Duty cycle  $\leq 2\%$
4. Essentially independent of operating temperature typical characteristics

Electrical Characteristic Curves

Fig. 1 Typical Output Characteristics




Fig. 2 Typical Output Characteristics




Fig.3 On-Resistance Variation with Drain Current and Gate Voltage




Fig. 4 Body Diode Forward Voltage Variation with Source Current




Fig. 5 Typical Capacitance Characteristics





Fig. 6 Typical Total Gate Charge Characteristics



Electrical Characteristic Curves

Fig. 7 Breakdown Voltage Variation vs. Temperature




Fig. 8 On-Resistance Variation vs. Temperature




Fig. 9 Maximum Drain Current vs. Case Temperature




Fig. 10 Maximum Safe Operating Area






Fig. 11 Transient Thermal Impedance




Outline Dimension : TO-220F



Unit : mm

**Marking Diagram**



First Line	WTC	Company Name	
Second Line	7N65FU	Product Code	
Third Line	BCOMF	1st ( Year Code )	A-2010 B-2011 C-2012 ...
		2nd ( Month Code )	A-Jan B-Feb C-Mar D-Apr E-May F-Jun G-Jul H-Aug I-Sep J-Oct K-Nov L-Dec
		3rd ( Lot Code )	0-1 , A-9
		4th ( Product Code )	M-MOS , T-Transistor
		5th ( Package Code )	X-TO-220, F-TO-220F
		6th ( Spec Code )	( Reserve )